

The background of the entire page is a close-up photograph of a textured, light-brown surface covered with numerous water droplets of various sizes. The droplets are in sharp focus, showing their rounded shapes and reflections. The overall tone is muted and earthy.

**WEATHERTUFF<sup>®</sup>**  
**CONSTRUCTION CHEMICALS**

**TUFFSIL**

**Silicone water repellent for masonry**

**WEATHERTUFF®**

# TUFFSIL

(SINGLE COAT TREATMENT)

**Description :** TUFFSIL is a very economical, water soluble of active silicone designed to impart water repellence of masonry surface. It reduces masonry maintenance cost with long term improved resistance to tropical weather. After application of TUFFSIL, water evaporates & it reacts with moisture & carbon-dioxide in the air to form an insoluble, invisible repellent Silicone film within 24 hrs.

**Advantages :** TUFFSIL treatment is effective on all types of masonry having open bricks Asb sheet, Teracota & Mangalore Tiles, Sand stone, plastered surface. On the treated surface, cement based or oil based paints may be applied.

- TUFFSIL keeps water on the run by forming an invisible Silicone Surface on the masonry wall. Collection of dust on the wall can be easily washed off
- TUFFSIL is ready to use by brush or spray directly on surface.
- TUFFSIL Preserve original colour or texture of treated surface.

Manufactured by :

**CHITRA INSULTEC PVT.LTD.**

Ahmedabad-380009. (Gujarat) INDIA.



Marketed by :

**WEATHERTUFF MARKETING**

202, Sarthak complex II, Nr. Swastik Char Rasta,

Navrangpura, Ahmedabad-380009. (Gujarat) INDIA.

Ph. : 079-26562100, Tele Fax : 079-26564777, 32998226

E-mail : [insultec@vsnl.net](mailto:insultec@vsnl.net) Web site : [www.weatherstuff.com](http://www.weatherstuff.com)

- TUFFSIL does not clog the pores of surface, so allows surface to breath.

**Direction of Uses :** Surface should be free from Oil, Grease, Loose Particles, Algae & Fungus. All joints & cracks must be sealed properly, We suggest using modified mortar (Like - Weathertuff's Diamond shield) for greater bonding. Apply one thick coat ready to use TUFFSIL on the surface. It can be applied by brush or spray. After application of TUFFSIL, the treated surface should be allowed to dry for minimum 24hrs. to develop maximum water repellency.

### Properties :

Colour	:	Clear liquid.
Sp. Gravity	:	0.98
Coverage	:	30 to 40 sq. Ft. per kg depending on porosity of substrate.
Self Life	:	12 months in sealed tin.
Packing	:	1 liter, 5 liter & 20ltr.