

# WeatherTuff®

Building Surface Solutions

## WEATHER SOL

For all Cementitious Surfaces

### Latex Base, Waterproof Undercoat

#### Weather Sol stabilizing solution

- (3 in 1) Water Thinnable coating/formulation
- Provides long-lasting and effective resistance to alkali and acidic attack and dampness
- Is recommended undercoat for all cementitious walls
- For any wall coating and cement coating
- Also can be used before re-coating

#### Technical Specification

Products data : Finish/Matte.  
Drying Time : Surface dry: 4 to 6 hours.  
Hard Dry : 24 to 48 hours.  
Covering capacity: 80 to 90 sq ft. per litre.  
Depending on the surface.

#### Uses For




Interior



Exterior



Terrace



Ceiling or Slab



R.C.C Structure



# WEATHER SOL

For all Cementitious Surfaces



## Application

1 or 2 coats as required after appropriate surface preparation. Keeping an over-coating interval of 4 hours between coats. The surface should be dry cut with sand paper before finish coats are applied. Diluted with water up to 15% to 20%.

## Advantages

### 3 in 1 Benefits

- Longer life to the wall
- Waterproofing undercoat
- Higher coverage to paints



## Available Size

10 Ltrs & 20 Ltrs

## Method of Application:



or



or



Brush

Roller

Spray.



**Marketed By WeatherTuff Pvt Ltd.**

202, Sarthak Complex II, Nr. Swastik Cross Road, Navrangpura, Ahmedabad  
- 380009. (Gujarat) INDIA. Ph: 91-79-2656 2100 Telefax : 91-79-2656 4777

**Manufactured By Chitra Insultec Pvt Ltd.**

3703/D, Phase 4, GIDC, Vatva, Ahmedabad- 382445. (Gujarat) INDIA