

SEALOXY PRIMER

For all Cementitious Surfaces

Acrylic, Waterbased, Waterproof Undercoat

Sealoxy Primer's Special Features

Sealoxy Primer gives 70 to 80 sq.ft coverage per Ltr on smooth surfaces.

Sealoxy white primer is 100% waterproofing undercoat. It gives better adhesion and longer life.

Sealoxy primer can be used as an undercoat for all paint.

Qualities

- o Acrylic
- Water based
- Waterproof
- Under caot

Uses



Interior



Exterior



Terrac



Ceiling or Stat





About Sealoxy Primer

Sealoxy Primer is an effective undercoat for indoor walls against minor moisture problems and for higher coverage of the paint. It is a thin coat which is flexible and stable. Sealoxy Primer is the first coat which is to be applied on a dry plastered wall. It fills the porosity in the plaster and makes it water resistant. To reduce overall painting cost, Sealoxy Primer is the best under coat.

Advantages

- Weathertuff Sealoxy Primer, an effective undercoat helps your indoor walls against minor moisture problems and keeps paint undamaged.
- It also helps preventing moisture penetration, when applied on outerwalls.
 DRY Sealoxy Primer film is thin, flexible, stable and white.
- When applied on dry plastered walls, it fills porosity of the plaster and make it water resistant.
- Flexible film of SEALOXY provides protection against expansion & contraction caused by variations of heat & cold in the atmosphere.
- Hence, the colour applied on its coating does not crack or chip.
- All water base colours can be applied on Sealoxy Primer.

Method of Application:



Dilute Sealoxy with water up to 15% to 20%.



Clean the surface



Apply ap



Apply one coat Seloxy
Primer by
Brush or Roller.

Allow the surface to be cured for 3-4hrs before applying any other paint.

Manufactured & Marketed By : Chitra Insultec Pvt. Ltd.

02, Sarthak Complex-II, Nr. Swastik Cross Road, Navrangpur Ahmedabad-380009. (Gujarat) INDIA. Phone: +91-79-2656 2100 | Telefax: +91-79-2656 4777

TOLL FREE NO.: 18001239010