

Weather Tuff®

Building Surface Solutions

WEATHER SOL

For all Cementitious Surfaces

Latex Base, Waterproof Undercoat

Weather Sol stabilizing solution

- (3 in 1) Water Thinnable coating/formulation
- Provides long-lasting and effective resistance to alkali and acidic attack and dampness
- Is recommended undercoat for all cementitious walls
- For any wall coating
- High flexibility due to Latex Base

Technical Specification

Products data : Finish/Matte.
Drying Time : Surface dry: 4 to 6 hours.
Hard Dry : 24 to 48 hours.
Covering capacity: 80 to 90 sq ft. per litre.
Depending on the surface.

Uses




Interior



Exterior



Terrace



Ceiling or Slab



R.C.C Structure



WEATHER SOL

For all Cementitious Surfaces

Application

1 or 2 coats as required after appropriate surface preparation. Keeping an over-coating interval of 4 hours between coats. The surface should be dry cut with sand paper before finish coats are applied. Diluted with water up to 15% to 20%.

Advantages

- 3 in 1 Benefits
- Longer life to the wall
- Waterproofing undercoat
- Higher coverage to paints



Available Size

10 Ltrs & 20 Ltrs

Method of Application:



Brush

or



Roller

or



Spray.



Manufactured & Marketed By :
Chitra Insultec Pvt. Ltd.

202, Sarthak Complex-II, Nr. Swastik Cross Road, Navrangpura,
Ahmedabad-380009. (Gujarat) INDIA.

Phone : +91-79-2656 2100 | Telefax : +91-79-2656 4777

Email : info@weathertuff.com | Web : www.weathertuff.com

TOLL FREE NO. : 18001239010